



Material Safety Data Sheet

PRODUCT AND COMPANY IDENTIFICATION

Product Name: SEAL & APPEAL
Manufacture: Tres Chic Nails
P.O. Box 24500
Rochester, NY 14624

Telephone Number: 585-247-6060

Version Number: 01
MSDS / Product Code: 10105
Issued Date: 01-01-08

Fax Number: 585-429-9897

TELEPHONE NUMBERS – 24 HOUR EMERGENCY ASSISTANCE:

Infotrac Domestic - 800-535-5053

Infotrac International - 352-323-3500

1. COMPOSITIONAL INFORMATION

<u>CHEMICAL IDENTITY</u>	<u>CAS NUMBERS</u>	<u>OSHA (PEL)</u>	<u>EXPOSURE LIMITS IN AIR</u>		<u>COMPOSITION AMOUNT (WT)</u>
			<u>ACGIH (TLV)</u>		
ACRYLIC COPOLYMER	NH	NONE	NONE		TS
BUTYL METHACRYLATE	97-88-1	NONE	NONE		TS
TOLUENE	108-88-3	150	100		TS
BUTYLACETATE	123-86-4	150 ppm	150 ppm		TS

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This information is based on findings from related or similar materials.

EFFECTS OF OVEREXPOSURE

INHALATION – Vapor extremely irritating

SKIN CONTACT – May cause burns

EYE CONTACT - Causes severe burns

3. FIRST AID MEASURES

First Aid for Eye	If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently for 15 min. with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.
First Aid for Skin	Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention.
First Aid for Inhalation	Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms persist, seek medical attention.
First Aid for Ingestion	If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Seek medical attention for advice about whether to induce vomiting. If possible, do not leave individual unattended.



Material Safety Data Sheet

4. FIRE FIGHTING MEASURES

Flash Point(°F/°C)

TAG Closed: 81 °F/27 °C

Method:

Extinguishing Media:

Foam, dry chemical, cold water spray.

Fire Fighting Instructions:

Wear self-contained breathing apparatus and protective clothing. USE WATER WITH CAUTION. Water spray may be used to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a safe distance and protected location.

Unusual Hazards:

Flammable. When exposed to heat and flame, material is a fire explosion hazard. It may produce toxic products CO, carbon dioxide and oxides of nitrogen. Vapors may cause a flash fire or ignite explosively. Vapors may travel a considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations.

5. ACCIDENTAL RELEASE MEASURES

Spill or Release
Procedures

Eliminate all sources of heat and ignition. Use absorbent material for spills and dike it, wash spill material into retaining containers. Place containers in a well ventilated area. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as sawdust. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.

6. HANDLING AND STORAGE

Handling

Keep containers cool and dry. Keep away from heat, light and ignition sources. Avoid breathing high vapor concentrations. Avoid prolonged or repeated contact with skin. Use only with adequate ventilation. Wash skin thoroughly after handling.

Storage

Store in a well ventilated area. Store @ 70 + 15 ° F, allow some air space above liquid level. Keep containers closed while not in use.

Explosion Hazard

Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.



Material Safety Data Sheet

7. EXPOSURE CONTROLS/PERSONAL PROTECTIVE EQUIPMENT

Engineering Controls	Use process enclosures, local exhaust ventilation or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment.
Personal Protective Equipment	
General	To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.
Eye/ Face Protection	Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type of safety glasses.
Skin Protection	Wear resistant gloves. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.
Respiratory Protection	A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Wear a NIOSH/MSHA or European Standard EN 149 approved full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.

Disclaimer:

The data contained herein is based upon information that Très Chic Nails believes to be reliable. Users of this product have the responsibility to determine the suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.