



# Material Safety Data Sheet

## PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** XTREME SEALER  
**Manufacture:** Tres Chic Nails  
P.O. Box 24500  
Rochester, NY 14624

**Telephone Number:** 585-247-6060

**Version Number:** 01  
**MSDS / Product Code:** 10108  
**Issued Date:** 01-01-08

**Fax Number:** 585-429-9897

## TELEPHONE NUMBERS – 24 HOUR EMERGENCY ASSISTANCE:

**Infotrac Domestic - 800-535-5053**

**Infotrac International - 352-323-3500**

## 1. COMPOSITIONAL INFORMATION

Chemical Identity	CAS Numbers	WT/WT %	ACGIH TLV/TWA	ACGIH TLV/STEL	OSHA PEL/TWA	OSHA PEL/CEILING	COMPANY RECOMMENDATION	SKIN
Acrylic Polymer in Toluene	NE	60.0-100.0	50 ppm Skin	75 ppm Skin	200 ppm Skin	150 ppm Skin	50 ppm Skin	50 ppm
Butyl Acetate	123-86-4	15.0-40.0	150 ppm	200 ppm	150 ppm	200 ppm	150 ppm	NE

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

Warning for Mixture: Flammable Liquid and Vapor.

#### FOR MIXTURE

##### Acute Hazards:

Eyes: Can cause severe irritation, conjunctivitis and corneal clouding.  
Ingestion: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. May cause abdominal spasms and other symptoms that parallel over-exposure from inhalation. Aspiration into lungs can cause chemical pneumonitis, which may be fatal.  
Inhalation: Inhalation of solvent vapors or mist can cause irritation of the nose, throat and lungs; headache; dizziness; drowsiness; fatigue; loss of coordination; unconsciousness.  
Skin: Solvent may be absorbed through the skin with the appearance of initial inhalation exposure symptoms.

##### Chronic Hazards:

Inhalation: High solvent vapor or mist concentrations can cause respiratory tract irritation, liver, kidneys and cardiovascular system.  
Chronic Poisoning: Anemia, decreased blood cell count and bone marrow hypoplasia. Liver and kidney damage may occur. Exposure may affect the developing fetus.



# Material Safety Data Sheet

Aggravation of Pre-existing Conditions

Persons with pre-existing skin disorders or impaired liver or kidney function may be more susceptible to the effects. Alcoholic beverage consumption can enhance the toxic effects. Chronic respiratory problems, such as asthma, emphysema or bronchitis. May aggravate existing skin conditions.

Note to Physician

Acute massive exposure to toluene can cause transient hematuria and albuminuria. Cardiac arrhythmias can occur after massive inhalation.

CARCINOGENICITY:

Toluene, the solvent for the Acrylic Polymer, is considered to be unclassifiable as to human carcinogenicity by IARC. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. None of the other components of this material are listed by IARC, NTP, OSHA, or ACGIH as carcinogens.

PRIMARY ROUTES OF ENTRY: Inhalation, Skin or Eyes.

### 3. FIRST AID MEASURES

First Aid for Eye

If product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. If irritation occurs, contact a physician.

First Aid for Ingestion

If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give anything by mouth to an unconscious person. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. Get medical attention immediately.

First Aid for Inhalation

Remove to fresh air. Seek immediate medical attention.

First Aid for Skin

If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately.

Clothing:

Remove contaminated clothing, wash thoroughly before reuse.

Treatment:

Treat symptoms conventionally, after thorough decontamination.

### 4. FIRE FIGHTING MEASURES

**Flash Point (°F/°C)**  
45°F/7°C For Toluene

**Flammable Limit (air vol %)**  
LOWER UPPER  
1.2 for Toluene 7.1 for Toluene

**Auto-ignition Temperature (vol%)**  
797°F, 425°C for Butyl Acetate

#### Method:

Extinguishing Media:

Carbon Dioxide, Dry Chemical, Alcohol Foam or Water Spray. Water spray may be ineffective on the fire, but should be used to cool fire-exposed containers and structures.

Fire and Explosion Hazards:

Eliminate sources of ignition. Above the flash point, vapor-air mixtures are explosive within the flammable limits. Sealed containers may rupture when heated. Vapors can flow along surfaces to distant ignition sources and flash back.

Special Fire Fighting Procedures:

This product is a flammable liquid. When involved in a fire, this product may ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. Do not enter fire area without proper protection. Fight fire from a safe location. Heat/impurities may cause pressure to build and/or rupture closed containers, spreading fire, increasing risk of burns/injuries. Structural firefighters must wear SCBAs and full protective equipment.

Sensitive to Mechanical Impact:

No

Sensitive to Static Discharge:

Yes



# Material Safety Data Sheet

## 5. ACCIDENTAL RELEASE MEASURES

Accidental Release: Before cleaning any spill or leak, individuals involved must wear appropriate Personal Protective Equipment (e.g., goggles, gloves). Deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g. sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Maximize ventilation (open doors and windows) and secure all sources of ignition. Place into appropriate closed container(s) for disposal in accordance with local, state and federal regulations. Wash all affected areas with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

## 6. HANDLING AND STORAGE

Handling Use good, local ventilation with a minimum capture velocity of 100 ft/min (30 m/min) at point of monomer release. Refer to Industrial Ventilation: A Manual of Recommended Practice published by the American Conference of Governmental Hygienist. Avoid contact with skin, eyes and clothing. Use good personal hygiene and housekeeping. Observe precautions found on label. Do NOT use localized heat source such as band heaters to heat/melt product. Do NOT use steam. Hot boxes or hot rooms are recommended for heating the product which can be set at a maximum temperature of 60°C/140°F.

Storage Store containers in a cool, dry location, away from direct sunlight, heat, sparks, flame, other light sources, or sources of intense heat. Keep container closed after each use. Check inhibitor levels periodically, adding to the bulk material if needed. Maintain at a minimum, the original 2-inch headspace in the product container and do not blanket or mix with oxygen-free gas as it renders the inhibitor ineffective.

Industrial Hygiene Practices Avoid prolonged contact with the product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.

## 7. EXPOSURE CONTROLS/PERSONAL PROTECTIVE EQUIPMENT

Ventilation Refer to Section 7 regarding the ventilation requirements for working with this product. Use local exhaust at processing equipment, including buffers, sanders, grinders and polishers. High temperature processing equipment should be well ventilated.

Respiratory Protection A respirator should be worn whenever workplace conditions warrant a respirators use. None required if airborne concentrations are maintained below the exposure limit listed in Section 2. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134 or other appropriate governing standard.

Eye Protection Depending on the use of this product, splash or safety glasses may be worn. If necessary, refer to U.S. OSHA 29 CFR §1910.133, or other appropriate governing standard. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.

Protective Gloves If anticipated that prolonged & repeated skin contact will occur during use of this product, wear chemical resistant gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, or other appropriate governing standards.



# Material Safety Data Sheet

Other  
Protective Equipment

No special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate governing standards. An eyewash station and a safety shower are recommended.

## 8. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Odor & Odor Threshold	PH	Odor Threshold	Boiling Point/ Freezing Point	Melting Point	Viscosity	Specific Gravity (H2O=1)
Clear, colorless liquid	Characteristic sweet or sour odor.	ND	ND	232°F, 111°C for Toluene	-107°F, -77°C for Butyl Acetate	NE	ND

Coefficient of Water/Oil Distribution	Vapor Pressure:	% Volatile W/W%:	Vapor Density (Air=1):	Evaporation Rate (BuAc=1)	Solubility In Water
< 3.0 for Toluene	22 mm Hg @ 20°C, 68°F for Toluene	~60%	Both solvents 3 to 4 times heavier than air	1.9 Toluene	Practically insoluble to slightly soluble.

## 9. STABILITY AND REACTIVITY

**Stability:**

Stable

**Hazardous Decomposition Products:**

Mainly Oxides of Carbon when burned.

**Conditions to Avoid:**

Heat, open flames, sparks, static electricity, sunlight, or other sources of ignition.

**Incompatibility (Materials to Avoid):**

Strong oxidizers agents

**Hazardous Polymerization:**

Will not occur

## 10. TOXICOLOGICAL INFORMATION

**TARGET ORGANS:**

For Acrylic Polymer in Toluene:

None Listed.

For Toluene:

Liver and Kidneys.

For Butyl Acetate:

None Listed.

**SENSITIVITY DATA:**

For Acrylic Polymer in Toluene:

None listed.

For Toluene:

Eye Human:

300 ppm.

Eye Rabbit:

870 µg. Mild.

Skin Rabbit:

435 mg. Mild

Skin Rabbit:

500 mg. Moderate.

For Butyl Acetate:

Eye Human:

300 ppm.

Eye Rabbit:

100 mg. Moderate.

Skin Rabbit:

500 mg/24H. Moderate.



# Material Safety Data Sheet

## MUTAGENICITY DATA:

For Acrylic Polymer in Toluene:

None listed.

For Toluene:

Inhalation Rat

Cytogenetic Analysis:

5400 µg/m<sup>3</sup>/16W.

Subcutaneous Rat

Cytogenetic Analysis:

9600 mg/kg/12D.

## REPRODUCTIVE TOXICITY DATA:

For Acrylic Polymer:

None listed.

For Toluene:

Has been demonstrated to be embryofetotoxic and teratogenic in laboratory animals.

Inhalation Mouse

TC<sub>Lo</sub>:

500 mg/m<sup>3</sup>/24H, 6-13D preg.

Inhalation Mouse

TC<sub>Lo</sub>:

1000 ppm/6H, 2-17D preg.

Inhalation Mouse

TC<sub>Lo</sub>:

400 ppm/7H, 7-16D preg.

Inhalation Mouse

TC<sub>Lo</sub>:

200 ppm/7H, 7-16D preg.

Inhalation Rat

TC<sub>Lo</sub>:

1500 mg/m<sup>3</sup>/24H, 1-8D preg.

Oral Mouse

TC<sub>Lo</sub>:

9 gm/kg, 6-15D preg.

Oral Mouse

TC<sub>Lo</sub>:

15 gm/kg, 6-15D preg.

Oral Mouse

TC<sub>Lo</sub>:

30 gm/kg, 6-15D preg.

For Butyl Acetate:

Inhalation Rat

TC<sub>Lo</sub>:

1500 ppm/7H, 7-16D Preg.

## TOXICITY DATA:

This product has NOT been tested on animals to obtain toxicology data. There is toxicology data for the components of the product, which is found in scientific literature. Some of this data is presented below.

For Acrylic Polymer in Toluene:

None listed.

For Toluene:

Inhalation Rat

LC<sub>Lo</sub>:

1000 mg/ m<sup>3</sup>/4H.

Inhalation human

LC<sub>Lo</sub>:

100 ppm

Oral Rat

LD<sub>50</sub>:

5000 mg/kg.

Skin Rabbit

LD<sub>50</sub>:

14000 mg/kg.

For Butyl Acetate:

Inhalation Human

TC<sub>Lo</sub>:

200 ppm.

Inhalation Rat

LC<sub>50</sub>:

390 ppm/4H.

Oral Rat

LD<sub>50</sub>:

14 gm/kg.

Oral Rat

LD<sub>50</sub>:

10768 mg/kg.

Skin Rabbit

LD<sub>50</sub>:

>17000 mg/kg.



# Material Safety Data Sheet

## 11. ECOLOGICAL INFORMATION

There is no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life. There is ecological data for the components of the product, which is found in scientific literature. Some of this data is presented below.

### AQUATIC TOXICITY:

For Toluene:

Rainbow Trout	LC <sub>50</sub> :	24 ppm/96H.
Fathead Minnow	LC <sub>50</sub> :	26 ppm/96H.
Bluegill Sunfish	LC <sub>50</sub> :	13 ppm/96H.
Algae	EC <sub>50</sub> :	>433 ppm/96H.
Daphnia Magna	EC <sub>50</sub> :	>11.5 ppm/48H.
For Butyl Acetate:		
Fish	LC <sub>50</sub> :	10-100 mg/L/96H.

### ENVIRONMENTAL FATE:

For Toluene:

When released into soil, may evaporate to moderate extent. When released into soil, expected to leach into groundwater. When released into water, may biodegrade to moderate extent. When released into air, may moderately degraded by reaction with photochemically produced hydroxyl radicals. When released into air, expected to have a half-life of less than 1 day. This material is not expected to significantly bioaccumulate.

For Butyl Acetate:

When released into the soil, this material is expected to readily biodegrade. When released into the soil, this material may leach into groundwater. When released into the soil, this material is expected to have a half-life of less than 1 day. When released into water, this material is expected to readily biodegrade. When released into the water, this material is expected to have a half-life between 1 and 10 days. This material has an estimated bioconcentration factor (BCF) of less than 100. When released into the air, this material may be moderately degraded by reaction with photochemically produced hydroxyl radicals.

## 12. DISPOSABLE CONSIDERATIONS

Waste Disposal Method: When discarded it is as a hazardous waste by the EPA under RCRA. Dispose waste material in accordance with Federal, State, and Local regulations.

Disposal of Empty Containers: Reuse of empty drums or containers is not recommended. Employees should be advised of the potential hazards due to residual flammable material, associated with empty containers. Dispose of all empty containers properly, in accordance with Federal, State and Local regulations.



# Material Safety Data Sheet

## 13. TRANSPORT INFORMATION

<b>DOT/UN Shipping Name:</b>	FLAMMABLE LIQUID, NOS (Toluene, Butyl Acetate)
<b>DOT/UN Class:</b>	3
<b>NA/UN NUMBER:</b>	UN 1993
<b>PACKING GROUP:</b>	II
<b>LABEL:</b>	Flammable Liquid
<b>IMDG CLASS:</b>	3.2
<b>EmS:</b>	3
<b>CERCLA RQ:</b>	For Component: Toluene: 1000 lbs. Butyl Acetate: 5000 lbs.

## 14. REGULATORY INFORMATION


SARA Reporting Requirements	Yes
SARA Threshold Planning Quantity	There are specific Threshold Planning Quantities for the components of this product.
TSCA Inventory Status	The components of this product are listed on the TSCA Inventory.
CERCLA Reportable Quantity (RQ)	Yes
Other Federal Requirements	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR.
Other Canadian Regulations	This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List.
State Regulatory Information	This product may contain components that are covered under specific state criteria.
<b>WARNING CODE</b>	F – Flammable
<b>RISK STATEMENTS</b>	R10 – Flammable R36/38 – Irritating to eyes and skin. R43 – May cause sensitization by skin contact.
<b>SAFETY STATEMENTS</b>	S3 – Keep in a cool place. S7/8 – Keep container tightly closed and dry. S9 – Keep container in a well-ventilated place. S15/16 – Keep away from heat, sources of ignition – No Smoking. S20 – When using do not eat or drink. S23 – Do not breathe spray. S24/25 – Avoid contact with skin and eyes. S29 – Do not empty into drains. S37/39 – Wear suitable gloves and eye/face protection.

# Material Safety Data Sheet


## 15. OTHER INFORMATION

Hazard Rating System (Pictograms)

**NFPA:**



**HMIS:**



Personal Protective Equipment: Gloves and Safety Glasses or Chemical Splash Goggles.

**ABBREVIATIONS:**

NA	Not Applicable	ND	Not Determined
NE	Not Established		
ppm	parts per million	G	Gallon
mg	Milligram	L	Liter
gm	Gram	mol	Mole
kg	Kilogram	μ	Micro
mm	Millimeter	p	Pico
Pa	Pascals	c	cento
LC	Lethal Concentration	LD	Lethal Dose
TC	Toxic Concentration	TD	Toxic Dose
BOD	Biological Oxygen Demand	COD	Chemical Oxygen Demand
Lo	Lowest	ThOD	Theoretical Oxygen Demand
TLm	Threshold Limit	IC	Inhibitory Concentration
DOC	Dissolved Organic Carbon		
H	Hours	M	Months
D	Days	Y	Years
W	Weeks		

**ABBREVIATIONS:**

ACGIH	American Conference of Governmental Industrial Hygienist
CPR	Controlled Product's Regulation
DSL	Canadian Domestic Substances List
NDSL	Canadian Non-domestic Substance List
IARC	International Agency for Research for Cancer
NOEL	No Observed Effect Level
NOAEL	No Observed Adverse Effect Level
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
TLV	Threshold Limit Value

**Disclaimer:**

The data contained herein is based upon information that Très Chic Nails believes to be reliable. Users of this product have the responsibility to determine the suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.